



SPECIFICATIONS

MODEL SIZE:

Length: 8' / 2.44 m

Width: 4' / 1.22 m, 3' / .914 m, 2' / .609 m

Thickness: ½" thick mat + ¼" cleat

MODEL WEIGHT:

Weight: 86 lbs/39.01 kg, 64.5 lbs/ 29.26kg, 51lbs/ 23.13 kg, 43 lbs/ 19.5 kg

Per Square Foot: 2.69 lbs (4'x8'mat)

COLORS:

Black, White

MATERIAL:

Black High Density Polyethylene (HDPE) post-industrial recycled plastic, naturally UV resistant due to the carbon black used for color. White plastic mats available also with UV protection.

TREAD PATTERN:

AlturnaMATS: diamond cleat design positioned at 90° angle to adjacent cleat.

VersaMATS: diamond cleat design on one side/flat oval slip resistant pedestrian tread on one side

SUPPORT STRUCTURE:

Matting incorporates multi-directional structural support (diamond cleat design) allowing for distribution or dispersion of PSE weight factors. Not intended for bridging.

WEIGHT LOADING:

There is not an actual PSI rating (depends on subsurface).

The ground cover mats have a load rating up 60 tons.

GROUND SURFACE:

AlturnaMATS are designed to be used on manicured landscapes, soft/wet grass, gravel, soil, concrete, asphalt, mud and also sandy conditions.

CONNECTION SYSTEM:

AlturnaMATS feature pre-drilled holes in each corner of the mat for the AlturnaMATS linking system. Mats can be connected end to end for a portable roadway or by connecting four corners to create a working platform. AlturnaMATS Turn-a-Links are made of steel and have a galvanized coating to prevent from rusting.

WARRANTY:

LIMITED LIFETIME WARRANTY against cracking and breaking under normal use.